



STELLAR AC FLOOR STAND L2 CHARGER DUAL PORT 19.2KW



ALWAYS **READY**. AN EV CHARGING NETWORK THAT'S ALWAYS **READY**. AN EV CHARGING NETWORK THAT'S ALWAYS **READY**. AN EV CHARGING NETWORK THAT'S

Technical Specifications



Product Information

Input/output power rating and current

2*19.2kW (240V AC*80A)

Input/output voltage

Output amperage adjustable via mobile app, from 6A to 80A
208V±15%; 240V±15%, 60Hz

Network type

L1/N+PE, L1/L2/PE

Input cord

Hardwired

Connector type

SAE J1772, 24.6' (7.5m) or 16.4' (5m)

Ground fault detection

20mA CCID

Protection

Overcurrent, overvoltage, undervoltage, integrated surge protection

Card reader

Optional: ISO 15693, ISO 14443, NFC

Power measurement accuracy

+/- 1.0% from 1% to full scale



General Characteristics

Enclosure rating

NEMA 3R

Operating altitude

6561.7' (2000m)

Operating temperature range

-40°F~+122°F (-40°C~+50°C)

Storage temperature range

-40°F~+185°F (-40°C~+85°C)

Mounting

Wall or floor using a pedestal

Dimensions (H×W×D)

24.60"x12.6"x6.7" (625×320×170mm)

User Interface

Status indication

LED / APP / LCD (8 inch, 1280*720 touch screen)

User interface

RED E Charge APP; RED E Charge Cloud Bluetooth,

Connectivity

Wi-Fi, Ethernet, 4G, RS485

Communication protocols

OCPP 1.6J (Can be upgraded to OCPP 2.0.1 later)

User authentication

APP, RFID card, Credit Cards (Optional)

Software Update

OTA updates via web portal

Certification and Standards

Safety and compliance

UL 2231-1, UL 2231-2, UL2594, NEC Article 625, CSA C22.2,

EMC compliance

UL 916 FCC 15 Class B

Certification

Energy Star, OpenADR 2.0b

Warranty

36 months, warranty extension possible

recharge.com

Customer Support (313) 262-6722

info@recharge.com

ALWAYS **READY**. AN EV CHARGING NETWORK THAT'S ALWAYS **READY**. AN EV CHARGING NETWORK THAT'S ALWAYS **READY**. AN EV CHARGING NETWORK THAT'S